





TAC Woodsman 700 Brush Chipper Specifications

6" Capacity Towable Disc Chipper, Hydraulic Feed Roll, Top Discharge

SPECIFICATIONS

Operating Weight 1,925 lbs

Chipping Capacity 6

Gross Engine Power 27 hp

Engine Options Kohler

FEATURES

24" Diameter x 1 1/4" thick disc with 2 full pockets

6" high by 6" wide chipper opening

Autofeed governor

300 degree swivel discharge

DIMENSIONS

Width 53.5"

Height 94"

Length (Operating) 130"

Length (Transport) 103"

ENGINE / DRIVE

Make/Model: Kohler Command Pro 27 27 hp @ 3,600 rpm Max hp: Max Torque: 42.3 ft-lb @ 2,400 rpm

Fuel: Gasoline Fuel Tank Capacity (gl): 2 Oil Capacity (qt): Cooling Medium: Air Cylinders:

Drive: Centrifigual Clutch / Belt

CUTTING SYSTEM

Disc Size: 24" dia. x 1.25" width Disc Speed (rpm): 1,567.74 rpm (2) Double Edged Knives: Anvil: 4 edges, 3/4" Steel

FEED SYSTEM

Infeed Opening: 6" x 6" Feed Table Height: 33" Feed Table Length: 56" Feed Wheel Diameter: 12.25 Feed Wheel Length: 6" Feed Rate (fpm): 150.57 Motor Displacement (cu. In.): 18.7 cu. in.

Feed Control: 4 Postion Bar w/ Autofeed Governor

Bar Actuation Force (lbs.):

Bar Positions: E-Stop, Forward., Stop & Reverse

FEED SAFETY SYSTEM

Bottom Feed Stop Bar: 10 Ga. Steel Bar Actuation Force (lbs.): 34

Reset Method: Momentary Push Button

DISCHARGE SYSTEM

Discharge Height: 94" Chute Rotation: 300°

Manual (Standard Latch) Rotation Type:

CHASSIS

Frame: 7 Ga. Steel 2" Ball Coupler Hitch Type: Tool Box:

8" x 7" - 5 bolt hub Wheels: 20.5 x 8 Tires:

Axle: 2,000 lb torsion axle

HYDRAULIC

System: Open Center

Hydraulic Tank Capacity (gl): 8

Filtration: 10 Micron Pump (gpm): System Relief (psi): 2,500

ELECTRICAL

19V System Voltage:

Battery: 12V 800 CCA

Lights: Turning, license, brake, tail and side marker

WEIGHTS

Tongue Weight (lbs):


Operating Weight (lbs.): 1,925


DIMENSIONS


Width: 53.5" Height: 94" 130" Length: Transport Length:

TEREX®

TAC Woodsman 700







www.terex.com/environmental-equipment

Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and Terex makes no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights are reserved. Terex is a registered trademark of Terex Corporation in the USA and many other countries.