





TBC 440 Biomass Whole Tree Chipper

Engineered and constructed for forestry and land clearing applications.

SPECIFICATIONS		FEATURES		DIMENSIONS	
Operating Weight	59,500 lbs	Drum Size	50" Diameter x 45" Wide	Width	10' 2"
Gross Engine Power	540-765 hp	Infeed Opening	32" High x 45" Wide	Height	11'0"
Engine Options	Caterpillar	Feed Control	Eaton FX with Radio Remote	Length	39' 10"
	Cummins	Chute Rotation	90 degree swivel discharge		

ENGINE / DRIVE

CAT, Cummins Make/Model: ► HP: 540-765

► Fuel: Diesel ► Fuel Tank Capacity (gl): 105 gallons ▶ Oil Capacity (qt): 60

Cylinders: Disc Clutch with Belts

CUTTING SYSTEM

Drum Size: 50" dia. x 45" wide 700 rpm Drum Speed (rpm):

Knives: (9) Adjustable Knives 4 edges, 1" Steel Anvil:

FEED SYSTEM

Infeed Opening:Feed Table Height: 32" high x 45" wide

51" 144" Feed Table Length: Feed Wheel Diameter: 30" 44" Feed Wheel Width: Feed Rate (fpm): 120

Motor Displacement (cu. in.) 6.5 cu. in.

Remote with Auto Feed Feed Control: DISCHARGE SYST 11" 0' Discharge Height:

Chute Rotation:

90 Degrees Rotation Type: Hydraulic **CHASSIS** Frame: Tube

► Hitch Type: 5th Wheel Standard Tool Box: Wheels: Tandem Duals ▶ Tires: 11R-24.5

Axle: (2) 20,000 lb. spring axle

HYDRAULIC

Svstem: Closed Center Hydraulic Tank Capacity (gl): 150 gl

Filtration: 10 Micron Return / 150 Micron Suction

Pump - Direct Drive (gpm): (2) Pressure Compensated 30 gpm

System Relief (psi): 2,500 and 4,100

O-Ring / O-Ring Face Seal ▶ Hydraulic Connections:

ELECTRICAL

System Voltage: 24V

► Battery: (2) 12V 1,400 CCA

Trailer Plug Connections: 7-Pole

Lights: Turning, license, brake, tail and side marker.

WEIGHTS

Operating Weight (lbs.): 59,500 lbs

DIMENSIONS

▶ Width: 10'2" ► Height: 11'0" Length: 39' 10"







1/8



TBC 440





www.terex.com/environmental-equipment

Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and Terex makes no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights are reserved. Terex is a registered trademark of Terex Corporation in the USA and many other countries

