



TEREX® | FINLAY



TC-65

TC-65 TRACKED CONVEYOR

SPECIFICATION:


Conveyor Length:	20m (65' 7")
Belt Width:	1.05m (42")
Net Engine Power:	(Tier 3) 36.4kW (45hp)
Max Discharge height:	10m (32' 10") @ 28°

TC-65 TRACKED CONVEYOR



CONVEYOR

Conveyor Length	20m	65'7"
Belt Width	1050mm	42"
Conveyor Drive	Hydraulic	800cc
Discharge Height @ 24°	8.7m	28'6"
Max Discharge Height @ 28°	10m	32'10"
Capacity	Up to 400 TPH	
Hydraulic Folding Head Section		
Belt Type	Plain: 3 Ply	
Polyurethane tensioned belt cleaner		
Hydraulic feed in height adjustment		
Hydraulic fold over for Transport		
Hydraulic conveyor angle adjustment		
40 degree rollers		
Variable speed control		
Feedboot with removable 6mm steel wear liners		



CHASSIS

Tracks	2.9m centres x 400mm shoe
2 Speed Track Motor	
Lower Speed	0.9Km/h
Higher Speed	1.6Km/h

GENERAL

Heavy duty undercarriage unit with 400mm wide tracks
External conveyor belt adjustment
Engine prestart delay & siren
Low level greasing
Emergency stops (4 nr)
Machine Painted, Finlay Orange RAL 2002
Safety guards in compliance with machinery directive

Full Length Conveyor Skirting



POWERUNIT

Diesel Hydraulic	
Engine (Tier 3)	Deutz D2011 L04I - 36.4kW (45hp)
Fuel Tank Volume	200 litres
Hydraulic Oil Cooler	Standard



Head Drum Guards and Dust Covers



Feed Boot Extension



Transport mode

OPTIONS EQUIPMENT

Deutz TD 2.9 L04 45kW (60hp) Tier 4 Final Engine

6mm AR400 Steel Wear Feedboot Liners

20mm Rubber Wear Feedboot Liners

Feedboot Extension c/w Steelwear Liners

Feedboot Extension c/w 20mm rubber Wear Liners

Feedboot Extension c/w 6mm AR400 Steelwear Liners

Impact Rollers at Feedboot area

Blade type / Primary scraper

Conveyor fitted with Chevron belt 3 ply x 4+2 covers

Conveyor fitted with Heavy duty plain belt 3 ply x 5+2 covers

Conveyor Under Guarding up To 2.5 Meters @12degree incline

Conveyor Head drum Guarding

Conveyor Dust covers

Conveyor Water Dust Suppression (Spray bar only)

Conveyor Full length skirting

Powerunit c/w Hydraulic oil, Century 100 - (Recommended for ambient temperatures between +15 to +50°C)

Radio remote control system for crawler tracks


Pull cord emergency stop

Special paint colour (if different from above). RAL must be specified on order



Working mode

TRANSPORT DIMENSIONS



MACHINE WEIGHT: 11,300kg (24,912lbs)



WORKS FOR YOU.™



TEREX | FINLAY

www.terexfinlay.com

TC-80